



# CP350SLG STANDBY UPS SYSTEM

Offers energy savings, battery backup and surge protection.



The CyberPower Standby CP350SLG uninterruptible power supply (UPS) safeguards PCs and other electronics (monitors, cable DSL/ modems, VoIP routers, fax machines, and home theater equipment) from blackouts, brownouts, surges, spikes, sags, and other power abnormalities.

This UPS system is ENERGY STAR® qualified with patented GreenPower UPS™ High Efficiency circuitry to save on energy costs by reducing energy consumption and heat buildup.

A Three-Year Warranty ensures that this UPS has passed our highest quality standards in design, assembly, material and workmanship, further protection is offered by a \$75,000 Connected Equipment Guarantee.

### TYPICAL APPLICATIONS

- Desktop Computers
- Home Networking/VoIP
- Personal Electronics

### FEATURES

- 350 VA/225 W
- Standby Topology
- GreenPower UPS™
- ENERGY STAR® Qualified
- Full-time Surge Protection and Battery Backup
- Compact Form Factor
- 6 Outlets
- EMI/RFI Filters
- Three-Year Warranty

## SPECIFICATIONS

GENERAL	
UPS Topology	Standby
Energy Saving	GreenPower UPS™ High Efficiency
ENERGY STAR® Qualified	Yes
INPUT	
Voltage	96 V-140 V
Frequency	47 Hz - 63 Hz
Circuit Breaker	10 Amp
Plug Type	NEMA 5-15P
Plug Style	Right Angle, 45° Offset Right
Cord Length	5'

OUTPUT	
VA	350
Watts	255
On Battery Voltage	120 V ± 5%
On Battery Frequency	50/60 Hz ± 1%
On Battery Waveform	Simulated Sine Wave
Outlets - Total	6
Outlets - Type	NEMA 5-15R
Outlets - Battery & Surge Protected	3
Outlets - Surge-Only Protected	3
Outlets - Widely Spaced	2

# CP350SLG STANDBY UPS SYSTEM



## SPECIFICATIONS CONT.

### OUTPUT CONT.

Overload Protection	Internal Circuitry Limiting/ Circuit Breaker
---------------------	---

Transfer Time	4ms
---------------	-----

### BATTERY

Runtime at Half Load (min)	8
-------------------------------	---

Runtime at Full Load (min)	2
-------------------------------	---

Battery Type	Sealed Lead-Acid
--------------	------------------

Battery Size	12 V/3.6 Ah
--------------	-------------

Battery Quantity	1
------------------	---

User Replaceable	No
------------------	----

Typical Recharge Time	8 Hours
-----------------------	---------

### SURGE PROTECTION & FILTERING

Surge Suppression	810 Joules
-------------------	------------

EMI/RFI Filtration	Yes
--------------------	-----

### MANAGEMENT & COMMUNICATIONS

HID Compliant USB Port	No
------------------------	----

Serial Port	No
-------------	----

Cable Management	None
------------------	------

LED Indicators	Power On, Wiring Fault
----------------	------------------------

### MANAGEMENT & COMMUNICATIONS CONT.

Audible Alarms	On Battery, Low Battery, Overload, UPS Fault, Replace Battery
----------------	---

Software	None
----------	------

### PHYSICAL

Form Factor	Compact
-------------	---------

Keyhole Mounting Slots	No
------------------------	----

Dimensions (WxHxD) (in.)	7.1 x 4.3 x 3.2
-----------------------------	-----------------

Weight (lbs.)	3.5
---------------	-----

### ENVIRONMENTAL

Operating Temperature	32°F to 104°F/0°C to 40°C
-----------------------	---------------------------

Operating Relative Humidity	0%-90% (Non-condensing)
--------------------------------	-------------------------

### CERTIFICATIONS

Safety	UL1778, cUL 107.3, FCC DOC Class B
--------	---------------------------------------

Environmental	RoHS Compliant
---------------	----------------

### WARRANTY

Product Warranty	Three-Years Limited
------------------	---------------------

Connected Equipment Guarantee	Lifetime
----------------------------------	----------

CEG Amount	\$75,000
------------	----------