

PondMAX[®]

PRODUCT LAUNCH

NEW

PaintMAX Black Pond Paint & Sealer

PONDMAX POND PAINT & SEALER CONTAINS ADVANCED ACRYLIC POLYMERS AND TITANIUM NANO-PARTICLES FOR A SUPERIOR DIRT AND ALGAE RESISTANT FINISH.



ALGAE
RESISTANT



QUICK
DRYING



AQUATIC
SAFE

BEFORE YOU START

Make sure your concrete pond is clean, dry and free from loose or flaky material. Fill all large cracks with PondMAX quick setting gap filler and allow to dry. It is advisable to use a waterproofing compound when constructing all new concrete ponds.

HOW TO USE

Stir PondMAX PaintMAX well and apply to concrete surface using brush or roller. A second coat may be applied the next day for superior results. For previously painted pond surfaces, make sure all old paint is thoroughly rubbed down to provide key for new paint.

Ideal temperatures for application should be between 8°C - 25°C.

Wash all brushes and equipment with water immediately and store remainder of paint in frost free conditions.

COVERAGE

1 litre covers up to 10 sq.metre depending on your ponds surface finish.

DRYING TIME

On warm days PondMAX PaintMAX will be dry in 1 hour and can be re-coated so the whole pond may be finished in one day. However newly painted ponds should be left a day before filling with water.

SAFETY

Ensure good ventilation and rain free conditions during application and drying.

Avoid contact with skin and eyes. Wear eye protection and if contacted wash off with soap and water. If swallowed seek medical advice. Keep out of reach of children.

- Paint & Seal concrete ponds in one application
- Superior coverage
- Dirt & Algae resistant finish

AVAILABLE IN
1L & 5L BLACK OR CLEAR



WATERGARDENING TO THE MAX



WWW.AQUATECEQUIPMENT.COM