

ProTac

Self Adhering Membrane Strip /Culvert Bandage

TECHNICAL DATA SHEET	TDS G 001 050
ISSUE NUMBER	03
DATE	OCTOBER 2016

DESCRIPTION

ProTac is a self adhering waterproofing membrane used in conjunction with resurfacing and overlaying operations and in pipe/culvert bandage operations to seal joints. It is comprised of a stress absorbing geotextile fabric that is combined with rubberised bitumen to produce a composite membrane that bonds tenaciously to clean, dry surfaces.

APPLICATION

Applications include crack sealing of many surfaces prior to surface overlaying or backfilling in applications such as:

- Road surfaces
- Lane widening joints
- Other paved surfaces such as runways and carparks
- Bridge decks and pipe / culvert joint sealing
- Sealing of bridge girder joins prior to surfacing

TYPICAL PROPERTIES

PROPERTY	TEST METHOD	UNIT	TYPICAL VALUE
Grab Tensile Strength	AS3706.2	N	900
Thickness	AS3706.1	Mm	2.0
Mass Per Unit Area	AS3706.1	Kg/m ²	2.2
Dimensions		M	0.3 x 15.24

Other widths of ProTac available upon request.

DISCLAIMER: All information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Cirtex Industries Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Cirtex Industries Ltd have a policy of continuous development so information and product specifications may change without notice.