

PaveSeal

Paving Fabric

TECHNICAL DATA SHEET	TDS G 001 049
ISSUE NUMBER	04
DATE	OCTOBER 2016

CHARACTERISTIC	TEST STANDARD	UNITS	AS240P	AS280P
TENSILE PROPERTIES				
Grab Strength	AS 2001.2.3	N	500	700
Elongation	AS 3706.4	%	> 40	> 40
Grating	Austrroads	-	900	1350
PHYSICAL PROPERTIES				
Polymer		-	Polyester	Polyester
Softening Point		°C	> 230	> 230
Mass	AS 3706.1	g/m ²	140	200
Thickness	AS 3706.1	mm	≥ 1.8	≥ 2.3
Standard Roll Size		m	6 x 100	6 x 100
Nominal Roll Weight		kg	95	125

The product properties listed on this data sheet are typical values derived from testing over long periods of time.

These test methods used to measure the properties of ProPave Paving Fabric are current recognised international standards.

DISCLAIMER: All information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Cirtex Industries Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Cirtex Industries Ltd have a policy of continuous development so information and product specifications may change without notice.