

Gabions

Woven Hexagonal Mesh Gabion Zinc Galvanised PVC Coated 8/2.7

TECHNICAL DATA SHEET	TDS G 001 025
ISSUE NUMBER	03
DATE	SEPT 2015

MANUFACTURE

Link Gabions shall be manufactured from double twist hexagonal woven wire mesh in accordance with EN 10223-3.

MESH SIZE

The mesh openings should be hexagonal and of nominal dimension of 80mm x 100mm and conform to EN 10223-3.

MESH WIRE

The nominal mesh wire for the body of the gabion should be 2.7mm in diameter and of a nominal 3.4mm for the selvedge wire. Both the body wire, selvedge wire and lacing wire should be in accordance with EN 10218-2 and EN 10223-3. The addition of PVC coating will increase all stated wire diameters by 1mm.

CORROSION PROTECTION

Zinc galvanised to EN 10244-2 Class A (245g/m²) with an extruded grey PVC coating of mean wall thickness of 0.5mm. PVC coating to EN 10245-2.

JOINTING

All jointing and connections should be formed with continuous 2.2mm (body wire) PVC coated zinc galvanised lacing wire and/or high tensile 3mm diameter stainless steel "C" rings.

DIAPHRAGMS

Fixed at 1m c/c across the gabion width for all gabions equal to or greater than 2m in length.

BBA APPROVAL

Link Gabions made from PVC coated hexagonal wire mesh is BBA certified for up to 120 years design life. BBA Agreement Certifies No. 00/3682 and 99/R117 (Roads and Bridges) refer.

STANDARD SIZES (NOMINAL)

LENGTH	WIDTH (M)	HEIGHT (M)
1	1	1
2	0.5	0.5
2	1	0.5
2	1	1
4	1	0.5
4	1	1



Member -
American Fencing Association



DISCLAIMER: All information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Cirtex Industries Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Cirtex Industries Ltd have a policy of continuous development so information and product specifications may change without notice.