

RainSmart

30mm Drainage Cell

TECHNICAL DATA SHEET	TDS G 001 018
ISSUE NUMBER	03
DATE	SEPT 2015

DESCRIPTION: Nerocell 30mm drainage cell is used in many horizontal drainage applications. The product has a high crush strength to support heavy loads with a unique cup structure which provides passive irrigation during prolonged dry weather periods. Nerocell has been designed to provide optimal flow conditions with unique panel geometry. Nerocell comes in a large panel size (500mm x 600mm) with integral clips for fast and easy installation.

APPLICATION

- Podium/plaza drainage
- Rooftop garden drainage
- Planter box drainage
- Vertical drainage panels behind walls

The modular drainage cell system replaces traditional heavy mineral drainage layers with one lightweight, easy to install system

TYPICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUE
Panel Width		500mm
Panel Length		600mm
Panel Height		30mm
Surface Void Area		68% void
Internal Void Ratio		95%
Material		90% recycled polypropylene + 10 % proprietary mix
Colour		Black
Biological & Chemical Resistance		Unaffected by moulds and algae, soil-borne chemicals, bacteria, bitumen, oils & light acid or alkaline solutions
Service Temperature		-10°C to 85°C
Compressive Strength/Ultimate Load	ASTM D 1621	> 135 t/m ²
Flow Rate	ASTM D 4716	> 18.95l/m.s @ $i = 0.01$

DISCLAIMER: All information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by CirteX Industries Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. CirteX Industries Ltd have a policy of continuous development so information and product specifications may change without notice