

# TWO NEEDLE LOCKSTITCH MACHINE

**T828**

**42 - 064**

**M**

**L**

**/**

**C**

## 机种别 Model

T828	双针平车 High speed two needle lockstitch machine
T8200	微油式雙針平車 Minimum lubrication type two needle lockstitch machine
DT8200	直驅微油式雙針平車 Direct-drive, minimum lubrication type two needle lockstitch machine



## 车缝布料 Sewing Material

L	薄布料 Light
M	中厚布料 Medium
H	厚布料 Heavy

## 旋梭 Hook

L	敞開式 Latch type
-	有蓋式 Cap type

## 自动切线 Auto thread trimmer

	機型 Machine Series	撥線 Thread Wiper	抬壓腳 Presser foot lifer
C	T828	V	V
C-11	DT8200	V	
C-13	DT8200	V	V

## 功能 Function

规格 Sub-class	针送 Needle feed	标准旋梭 Standard hook	大旋梭 Big hook	倒缝 Reverse feeding	角缝 Split needle bar
42	V	V	-	V	-
45	V	V	-	V	V
72	V	-	V	V	-
75	V	-	V	V	V

# T828 SERIES FEATURES

针送式送料，缝目准确，并可自由调整大小，缝目稳定美观

The design of needle feed mechanism moves with simple operation , excellent stitching and precise stitch-length.

采用旋转水平式旋梭，并附自动给油装置

Adopting fully rotating horizontal axis hook , slide type thread take-up as well as automatically lubricating system.

附有检视底线用的窗口，方便查看梭仔线的余量

Convenient window for monitoring bobbin thread volume.



一般平缝  
General plain seaming

T1	mm	mm	mm		Needle No. DPX5	S.P.M. (Max)	一般车选配 General M/C Option	自动切线车选配 Auto Thread Trimmer M/C Option					选配 Optional	
			手动 Hand	自动 Auto			离合器 马达 Clutch Motor	代码 No.	操控面板 Control Panel	快速倒缝 Reverse Feeding	拨线杆 Wiper	自动 抬押脚 Auto Lifter	伺服马达 Servo Motor	桌板 Table
T828-42-xxxMx	4	29.0	7	10	#14	4000	.T32xxDx (Clutch motor)  .TSA-550 (Simplified Servo motor)	C	C-300M-A2	V	V	V	TC10xEH	T828-T1
T828-42-xxxHx	5	30.7			#22	3000								
T828-45-xxxMx	4	35.0			#14	4000								
T828-45-xxxHx	5	30.7			#22	3000								
T828-72-xxxMx	7	35.0		10- 13	#14	3000								
T828-72-xxxHx	7	30.7			#22	3000								
T828-75-xxxMx	7	30.7			#14	3000								
T828-75-xxxHx	7	30.7			#22	3000								